

Pigtails OM4



View the product
on the website

DETAILS

Key features

OM4 multimode pigtails terminated in-house with ST, SC, FC, or LC connectors, available in both PC and APC configurations. They are supplied in the standard length of 1.0 metre, with the option of longer lengths on request.

TECHNICAL FEATURES

Characteristic	Value
Connector	SC, LC, ST, FC Pc e Apc
Jacket	LSZH (Low Smoke Zero Halogen), purple color
Structure	Tight Buffer of 900 ?m or Easy Strip version on request
Standard	TIA/EIA 492AAAA e IEC60793-2-10
Insertion Loss	0,25 dB
Attenuation (dB/km)	2.8 @ 850nm / 0.8 @ 1300nm
Bandwidth OFL (Mhz/km)	3500 @ 850nm / 500 @ 1300nm
Diameter (µm)	900 ± 50
Tensile Strength (N/100mm)	500
Operating Temperature	-20°C / +60°C
Tension Force (N)	6

CODE TABLE

Code	Description	Connector	Lenght
80028-1-OM4	Pigtails 50/125 OM4	SC	1
80031-1-OM4	Pigtails 50/125 OM4	FC	1
80034-1-OM4	Pigtails 50/125 OM4	ST	1
80037-1-OM4	Pigtails 50/125 OM4	LC	1